



# NC30

Finn-Power NC-machines have proven to be the most reliable and widely used nut crimping machines in the industry. NC-machines provide fast and accurate crimping for fitting manufacturing.

NC30 is equipped with longer master dies and has bit more opening and force than NC20. NC30 can be used also for other applications with short crimping length eg. connectors, small hoses, rings, tubes and sensors.

Adjustable back stop enables quick set up for different products. A special centering pin, selected according to ferrule size, can be used during the crimping.

Also available as Z-model with separate crimping head and hydraulic unit.

TECHNICAL DATA		DIMENSIONS (LxWxH)	
Crimping range (mm) <sup>1)</sup>	12-63	Standard (mm)	835x885x997
Crimping range (inch) <sup>1)</sup>	0.47-2.48	Standard (inch)	32.9x34.8x39.3
Max. crimping force (kN)	660	Z-model head (mm)	406x359x395
Max. crimping force (tonnage)	66	Z-model hydraulic unit (mm)	597x436.5x651
Cycle time 10 mm (s) <sup>2)</sup>	1.4 (S-model: 0.6)	Z-model head (inch)	15.9x14.1x15.6
Hose size ID (inch)	2	Z-model hydraulic unit (inch)	25.6x17.2x23.5
Die set series	NC30	WEIGHT (KG/LBS)	
Max. opening (mm) <sup>3)</sup>	+26	Standard	288/529
Max. opening without dies (mm)	125	Z-model head	129/284
Master die D/L (mm)	99/35	Z-model hydraulic unit	101/222
Master die D/L (inch)	3.90/1.38		
Motor Power (kW/HP)	4.0/5.5		
Oil tank volume	50 l		
Z-model availability	YES		

- 1) With standard dies. Crimping range can be increased with special dies.
- 2) Theoretical with 10mm cycle.
- 3) Maximum opening is the total die travel. Add this value to the minimum crimping diameter of the die set used. The result is the maximum opening of the machine with die set in place.

## CONTROL

ICC

## STANDARD FEATURES


Foot pedal (Standard)  
Mechanical back stop device  
Pressure crimping ICC1  
Step crimping ICC2

## OPTIONS

Foot pedal (Z-model)  
Auto greasing G3  
Oil cooler \*\*  
\*\* Will have impact on motor size, hydraulic unit dimensions and weight.

## OPTIONS (ICC)

Quality control ICC3  
Graphical quality control ICC4  
Remote control unit  
Interface pack ETH (Communication TCP/IP & UDP)  
Bar Code Reader BCR



## DIE SET NC30-SERIES

DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
702044/12	12	3	12.0-14.0
702044/14	14	3	14.0-16.0
702044/16	16	4	16.0-19.0
702044/19	19	4	19.0-22.0
702044/22	22	4.5	22.0-26.0
702044/26	26	4.5	26.0-30.0
702044/30	30	5	30.0-34.0
702044/34	34	5	34.0-39.0
702044/39	39	5	39.0-45.0
702044/45	45	5	45.0-51.0
702044/51	51	5	51.0-57.0
702044/57	57	5	57.0-63.0

In addition to the standard die sets, a wide range of special die sets is available on request.

**FURTHER INFO ON OPTIONS,  
PLEASE REVERT TO SPECIFIC PRODUCT CARD**

POWERCO.LILLBACKA.COM LILLBACKAUSA.COM