



CM75 SAFE

Finn-Power CM75 SAFE has the same capacity as in CM75 with added safeguard and motor brake. Safeguard opens only after blade rotation has stopped.

Service free electrical brake stops the blade in only 3 seconds.

Pusher movement speed can be quickly and easily adjusted to choose optimal cutting speed for every hose. The blade can be sharpened when necessary. The cutter has a built-in bin for collecting cutting waste.

See also QT-model.

TECHNICAL DATA

Max. hose size (inch)	2
Diameter (blade) external	520x4
Diameter (blade) internal	38
Max. hose OD	71
Motor Power (kW/HP)	7.5 / 10.0
Velocity, 50Hz	2840
Velocity, 60Hz	2840

DIMENSIONS (LxWxH)

mm	990x714x1318
inch	39.0x28.2x51.9

WEIGHT


kg/lbs	300/485
--------	---------

STANDARD FEATURES

- Toothed blade
- Adjustable pneumatic pusher speed
- Adjustable hose support
- Safeguard
- Motor brake

OPTIONS

- Measuring table (2 m segments)
- Fume extractor
- Smooth blade



Measuring table (left/right handed) as an option.

**FURTHER INFO ON OPTIONS,
PLEASE REVERT TO SPECIFIC PRODUCT CARD**

POWERCO.LILLBACKA.COM LILLBACKAUSA.COM